


TP6/EC Low Cost Standard Axial Component Former:

	MM		INCH	
	Min	Max	Min	Max
TP6/1-EC Standard Model Specifications:				
P	6.5	60	0.225	2.362
B	5.0*	13.0	0.196	0.511
c	1.2	-	0.047	-
L	-	50	-	1.968
d	0.4	1.3	0.015	0.051
D	0.4	16.0	0.015	0.629




***Note: Dim B can go to 3mm using special cutting disc - OL40071002**

Product Order Code: MOL23.OL01

TP6/4-EC Extra Reinforced Bending Specifications:


P	10.16	60	0.4	2.362
B	5.0	13.0	0.196	0.511
c	2.4	-	0.094	-
L	-	50	-	1.968
d	0.6	1.4	0.023	0.055
D	0.6	16.0	0.023	0.629



Product Order Code: MOL23.OL04

TP6/5-EC Reduced Cut, Variable Pitch Specifications:


P	6.5	60	0.255	2.362
B	4.0	13.0	0.157	0.511
c	1.2	-	0.047	-
L	-	50	-	1.968
d	0.4	1.0	0.015	0.039
D	0.4	16.0	0.015	0.629



Product Order Code: MOL23.OL05

TP6/6-EC Reduced Bending – Reduced Cut, Variable Pitch Specifications:

P	5.08	60	0.2	2.362
B	4.0*	13.0	0.157	0.511
c	0.8	-	0.031	-
L	-	50	-	1.968
d	0.4	0.8	0.015	0.031
D	0.4	10.0	0.015	0.390




***Note: Dim B can go to 2.5mm using special cutting disc – OL40071002 (Lead dia “d” Max 0.6mm)**

Product Order Code: MOL23.OL06

TP6/EC Low Cost Standard Axial Component Former:

TP6/7-EC Reduced Bending – Reduced Cut, Fixed Pitch Specifications:

P*	5.08	60	0.2	2.362
B	4.0	13.0	0.157	0.511
c	0.8	-	0.031	-
L*	-	50	-	1.968
d	0.4	0.8	0.015	0.031
D	0.4	10.0	0.015	0.390



*To be specified on order

Product Order Code: MOL23.OL07