



TP6/V Vertical Axial Component Cut & Bend Machine:

	MM		INCH	
	Min	Max	Min	Max
TP6/V/1 Specifications – Lead Diameter 0.5-0.8mm:				
A	2.0	6.0	0.078	0.236
L	-	15	-	0.590
F	3.0	8.0	0.118	0.314
D	0.5	3.0	0.019	0.118
d	0.5	0.8	0.019	0.031
P	2.54 Fixed		0.1 Fixed	




Product Order Code: MOL80.OL01

TP6/V/3 Specifications – Lead Diameter 0.5-0.8mm:				
A	2.5	6.0	0.098	0.236
L	-	15	-	0.590
F	3.0	8.0	0.118	0.314
D	0.5	5.0	0.019	0.196
d	0.5	0.8	0.019	0.031
P	3.8 Fixed		0.15 Fixed	




Product Order Code: MOL80.OL03

TP6/V/4 Specifications – Lead Diameter 0.5-0.8mm:				
A	3.0	7.0	0.118	0.275
L	-	15	-	0.590
F	3.0	8.0	0.118	0.314
D	0.5	8.0	0.019	0.314
d	0.5	0.8	0.119	0.031
P	5.08 Fixed		0.2 Fixed	



Product Order Code: MOL80.OL04

TP6/V/5 Specifications – Lead Diameter 0.5-0.8mm:				
A	4.0	7.0	0.157	0.275
L	-	15	-	0.590
F	3.0	8.0	0.118	0.314
D	0.5	10	0.019	0.393
d	0.5	0.8	0.019	0.031
P	7.62 Fixed		0.3 Fixed	




Product Order Code: MOL80.OL05

TP6/V Vertical Axial Component Cut & Bend Machine:

TP6/V/21 Specifications – Lead Diameter 0.8-1.3mm:


A	4.0	9.0	0.157	0.354
L	-	15	-	0.590
F	3.0	8.0	0.118	0.314
D	0.8	5.0	0.031	0.196
d	0.8	1.3	0.031	0.051
P	3.8 Fixed		0.15 Fixed	



Product Order Code: MOL80.OL21

TP6/V/22 Specifications – Lead Diameter 0.8-1.3mm:


A	5.0	9.0	0.196	0.354
L	-	15	-	0.590
F	3.0	8.0	0.118	0.314
D	0.8	8.0	0.031	0.314
d	0.8	1.3	0.031	0.051
P	5.08 Fixed		0.2 Fixed	



Product Order Code: MOL80.OL22

TP6/V/23 Specifications – Lead Diameter 0.8-1.3mm:

A	6.0	9.0	0.157	0.354
L	-	15	-	0.590
F	3.0	8.0	0.118	0.314
D	0.8	10	0.031	0.393
d	0.8	1.3	0.031	0.051
P	7.62 Fixed		0.3 Fixed	



Product Order Code: MOL80.OL23