



Professional Air Sprayable Seam Sealer Gun & Caulking Gun



ST-6640 For Cartridge
Air Caulking Gun (Metal)



ST-6641 For Cartridge
Air Caulking Gun (Plastic)



ST-66401 For Cartridge & Sachet
2 in 1 Air Caulking Gun
9" Aluminum Pipe (Rod Pull Type)



ST-66404 For Cartridge & Sachet
2 in 1 Air Caulking Gun
9" Aluminum Pipe (Rod Pull Type)



ST-66407 For Cartridge
Professional Air Caulking Gun
9" Aluminum Pipe



ST-66410 For Cartridge & Sachet
2 in 1 Professional Air Caulking Gun
with QC Exhaust Valve & Grip
9" Aluminum Pipe (Line Pull Type)



ST-66409 9" For Cartridge & Sachet
ST-66411 11" For Cartridge & Sachet
ST-66413 13" For Cartridge & Sachet
3 in 1 Air Sprayable Seam Sealer Gun
& Caulking Gun



ST-66412 For Cartridge
Air Sprayable Seam Sealer Gun & Caulking Gun
With Q.C. Exhaust Valve, Pin Regulator & Grip
Aluminum Pipe (Line Pull Type)

Pressure Valve Setting of 3 in 1 (Do not exceed 90 PSI) :

Beads	Sprayed Seam	Coating
Adjust blue valve (plunger air pressure) to: Narrow bead 3 - 4 Wide bead 5 - 6 Heavy bead 7 - 8	Adjust blue valve to 5 Adjust red valve to 2.5 - 3 Spray at a distance of 6 - 10 inches from the surface to minimize overspray	Adjust blue valve to 5 Adjust red valve to 3 - 4 Spray at a distance of 6 - 10 inches from the surface to minimize overspray

Specification:

Model No.	Capacity (ml)		Operated Air Pressure (psi)	Air Inlet	Air Hose
	Cartridge	Sachet			
ST-6640	310	-	45-90	1/4"	1/4"
ST-6641	310	-	45-90	1/4"	1/4"
ST-66401	310	310-400	45-90	1/4"	1/4"
ST-66404	310	310-400	45-90	1/4"	1/4"
ST-66407	310	-	45-90	1/4"	1/4"
ST-66410	310	310-400	60-90	1/4"	1/4"
ST-66409	310	310-400	60-90	1/4"	1/4"
ST-66411	400	310-500	60-90	1/4"	1/4"
ST-66413	500	310-600	60-90	1/4"	1/4"
ST-66412	310	-	60-90	1/4"	1/4"



Professional Air Grease Gun



ST-66364SC 400c.c.
ST-66364SCL 500c.c.

2 in 1 Single & Continuous shot Air Grease Gun
W/6" Metal Bend Spout
& 9" Flexible Hose



ST-66364SCP-18

ST-66364SCP 400c.c.

2 in 1 Single & Continuous shot Air Grease Gun
W/ PC clear tube, 6" Metal Bend Spout
& 9" Flexible Hose 400c.c.



ST-66364SCP-18

2 in 1 Single & Continuous shot Air Grease Gun
W/ PC clear tube & 18" Flexible Hose

*Not available 500c.c PC clear tube.
Proscription corrodible grease.
EX: Aeroshell 33 grease, Areoshell 7 grease, kydrol products, Brake fluid.*



Composite housing

ST-C630L 500c.c.
Single-shoot Air Grease Gun

ST-C630CL 500c.c.
Continuous Air Grease Gun



ST-6636 400c.c.
ST-6636L 500c.c.
Air Grease Gun



HT-6101

w/50°-0.5mm Dia
*Different nozzle size for option
ex. 90°-0.8mm, 50°-1.0mm, 50°-1.4mm Dia

HT-6101A1

w/50°-0.5mm & 90°-0.8mm Dia

Grease gun injection head with 100cc grease
Working Temperature (C°): -20° ~ 180°
Weight: 220g (0.48 lbs)



▶ Nozzle: 50°-0.5mm Dia
& 90°-0.8mm Dia



▶ Recommended for mechanical
and air tool maintenance.

ST-6636-6 400c.c.
ST-6636L-6 500c.c.
Air Grease Gun
W/6 Pcs Accessories

Specification:

★ Recommend Air Pressure: 6.2bar (90psi)

Model No.	Capacity		Size (mm L × mm φ)	Container Tube	Single Shot		Container Tube		Packing Pcs/Ctn/G.W./Cuft (kgs)
	Cartridge Loading (oz)	Bulk Loading (c.c)			psi	bar	psi	bar	
ST-66364SC	14	450	420×57.0	Alum	60~120	4.2~8.27	Max~2,500	Max~173	10Pcs/Ctn/19/2'
ST-66364SCL	15.8	500	420×63.0	Alum	60~120	4.2~8.27	Max~2,500	Max~173	10Pcs/Ctn/21/2.5'
ST-66364SCP	14	450	420×57.0	PC	60~120	4.2~8.27	Max~2,500	Max~173	10Pcs/Ctn/19/2'

Model No.	Capacity		Size (mm L × mm φ)	Container Tube	Input Pressure (working Pressure)		Output Pressure		Packing Pcs/Ctn/G.W./Cuft (kgs)
	Cartridge Loading (oz)	Bulk Loading (c.c)			psi	bar	psi	bar	
ST-C630L	16	500	410×57.5	Chrome Plated	40 ~ 100	2.8 ~ 6.9	1600 ~ 4000	110 ~ 276	10/Ctn/14/2.5'
ST-C630CL	16	500	410×57.5						10/Ctn/15/2.5'
ST-6636	14	450	410×49.0						10/Ctn/18.8/1.5'
ST-6636L	16	500	410×57.5						10/Ctn/19.6/3'